

Manufacturer	Oy Meclift Ltd
Type	ML5016SR
Standard colors	Orange (RAL2004) & Blue (RAL5002)

#### LIFTING PROPERTIES

Lifting capacity	kg	42,500
Load center	mm	1,600
Lifting height	mm	7,690
Reach	mm	Depending on boom structure

#### DIMENSIONS

Length	mm	11,700
Width	mm	4,000
Height (min)	mm	4,500
Ground clearance	mm	220
Weight	kg	64,000
Turning radius	mm	7,550

#### TECHNICAL SPECIFICATIONS

Power source	Diesel engine	
Manufacturer	Volvo	
Model	TWD 1230 VE	
Power rating ISO 2534	kW@rpm	310@2100
Peak torque	Nm@rpm	1860@1300
Transmission	Hydrostatic 4 wheel drive	
Driving speed	km/h	30
Service brake	Hydraulic motors and disc brake	
Parking brake	Disc brake	
Tyres		
Manufacturer	Nokian Heavy Tyres	
Model	HTS E-4 TL 6x18.00-25	
Specialities	Different boom constructions and lifting attachments available	

Oy Meclift Ltd  
Hepolamminkatu 51  
FI-33720 Tampere, Finland  
Tel +358 20 743 1120  
Fax +358 20 743 1121  
sales@meclift.fi  
www.meclift.fi